



Bluetooth V2.0 USB Adapter

Provides Class-1 and Class-2 with BQB Certification



Taiwan / Headquarters
TEL:886-2-7739-6888
FAX:886-2-7739-6887

China
TEL:8610-6213-9288
FAX:8610-6213-9231

U.S.A.
TEL:1-408-496-1105
FAX:1-408-980-1530

Latin America
TEL:1-786-845-8099
FAX:1-786-331-8490

Nederlands
TEL:31-499-377344
FAX:31-499-372647

Poland
Tel: +48(22)-6060-255
Fax: +48(22)-6060-254

U.K.
TEL:44-870-7740226
FAX:44-870-7740227



Key Features

- Bluetooth 2.0/1.2/1.1 compliant
- Increase data rate to 2M, 3Mbps.
- Co-existent with 802.11 wireless carrier with no interference.
- Work as an audio Gateway (In/Out) on PC, with Bluetooth Headset to use MSN, Skype, Netmeeting and other IM application.
- Listen to MP3 and other audio with Bluetooth Stereo Headset from PC.
- Allows user the ability to create a Bluetooth Personal Area Network with other compatible Bluetooth devices.
- Share/Edit/Print documents via Bluetooth.
- Access internet via Bluetooth Mobile phone with GPRS/ CDMA or Bluetooth enabled PC with internet connection.
- Browse the Internet/Check E-mails/Send Faxes/Play Games.
- Exchange or synchronize Personal Information Manager data with Bluetooth enabled Mobile phone or PC.
- Wireless connection via a serial cable/mouse/keyboard/Bluetooth stereo headset.

Model NO.	EB-DGC1	I	EB-DGC2
Chipset	CSR with Toshiba Bluetooth software		
Power Class	Class-1 (150M)		Class-2 (80M)
Data Transfer rate	3Mbps (Max)		
Antenna	Integrated antenna		
Dimension	59 x 7 x 19 mm		
Certification	BQB, FCC Class B, CE Mark		
OS Supports	Windows 98SE, Me, 2000, XP, Linux and Mac		

Bluetooth Profile Support: Personal Area Network, Headset, Audio Gateway, Dial-up Network, LAN Access, Human interface Device, PIM Item Transfer, PIM Synchronization, File Transfer, Generic Object Exchange, Object Push, Serial Port, Hardcopy Cable Replacement, Printer, FAX, Basic Image profile, AV Profiles (General Audio Video Distribution Profile, Advanced Audio Distribution Profile, Audio Video Remote Control Profile) are available on Win XP & 2000 only.